

copy 1

	L #	Hits	Search Text	DBs
1	L1	13	(result meaning) near10 decod\$3 near10 (instruction command) near20 (depend\$3 based alter\$3 modif\$6 chang\$3) near10 mode near10 (flag bit register)	USPAT; US-PGPUB
2	L3	24	decod\$3 near10 (instruction command) near20 (depend\$3 based alter\$3 modif\$6 chang\$3) near10 mode near10 (flag bit register)	EPO; JPO; DERWENT; IBM_TDB
3	L2	91	decod\$3 near10 (instruction command) near20 (depend\$3 based alter\$3 modif\$6 chang\$3) near10 mode near10 (flag bit register)	USPAT; US-PGPUB

	Document ID	U	Title	Current OR
1	JP 20010 35158 A	<input type="checkbox"/>	METHOD AND SYSTEM FOR ACCESSING MEMORY	
2	JP 10171 441 A	<input type="checkbox"/>	CHARACTER DISPLAY CONTROL CIRCUIT	
3	JP 08234 979 A	<input type="checkbox"/>	PROCESSOR HAVING BRANCH INSTRUCTION EXECUTING FUNCTION AND BRANCH INSTRUCTION CONTROL METHOD	
4	JP 04254 985 A	<input type="checkbox"/>	DRAM CONTROLLER	
5	JP 04102 982 A	<input type="checkbox"/>	MICROCOMPUTER	
6	JP 01283 647 A	<input type="checkbox"/>	DUPLICATED ERROR GENERATING DEVICE FOR MICROPROCESSOR	
7	JP 01037 627 A	<input type="checkbox"/>	REGISTER UPDATING MECHANISM	
8	JP 60096 030 A	<input type="checkbox"/>	DECODING SYSTEM	
9	JP 59003 642 A	<input type="checkbox"/>	CONTROL REGISTER PROCESSING SYSTEM	
10	JP 57059 205 A	<input type="checkbox"/>	NUMERIC CONTROLLER	
11	JP 56074 749 A	<input type="checkbox"/>	MICROPROGRAM CONTROLLING DEVICE	
12	DE 19932 465 C1	<input type="checkbox"/>	Arrangement for programming functional devices equipped with digital decoders changes decoder to programming mode using drive voltage on track with digital controller in reset state	
13	EP 10507 98 A1	<input type="checkbox"/>	Decoding instructions	
14	DE 19932 465 C	<input type="checkbox"/>	Arrangement for programming functional devices equipped with digital decoders changes decoder to programming mode using drive voltage on track with digital controller in reset state	
15	EP 10507 98 A	<input type="checkbox"/>	Decode unit for decoding instructions in a processor that can support three instruction modes has detector that temporarily allows first length instructions to be decoded without changing instruction mode held in register	
16	US 60121 38 A	<input type="checkbox"/>	Dynamically variable length CPU pipeline for executing multiple instruction sets	
17	JP 11154 393 A	<input type="checkbox"/>	Non-volatile semiconductor memory e.g. electrically erasable programmable read only memory EEPROM, used for recording of multimedia information - has controller which makes predetermined number as designated page unit when predetermined command for designating program unit is included based on decoding result of command decoder	
18	US 58023 60 A	<input type="checkbox"/>	Integrated circuit with digital processor for dynamic selection of instruction execution intervals - has decode stage coupled to execute stage with mode input for selecting number of clock cycles taken to execute flag-modifying instruction	
19	US 51230 96 A	<input type="checkbox"/>	Data processor with addressing mode decoding function - modifies entry address of microinstruction when addressing mode of operand detected to enable entry address	
20	JP 02011 076 A	<input type="checkbox"/>	Sound decoder for MUSE television receiver - operates muting circuit when state change of mode command bit in control code is detected NoAbstract Dwg 0/2	

	Docum ent ID	U	Title	Current OR
21	DE 35007 41 A	<input type="checkbox"/>	Integrated circuit for floppy disc drive control - has registers to handle control and data transfers between disc drive and computer operating with status interlock stage	
22	SU 10658 52 A	<input type="checkbox"/>	Multi-computer network computer interfacing unit - has memory data input coupled through high-way with coupling amplifier data outputs to group lines	
23	WO 83030 17 A	<input type="checkbox"/>	Computer with static cache - automatically maps memory contents into machine registers during program execution	
24	EP 40703 A	<input type="checkbox"/>	Enhancement of 370 type data processor - reduces overhead incurred by multiple users by permitting program in one address space to obtain access to data in another address space	

	Docum ent ID	U	Title	Current OR
1	US 20030 02116 3 A1	<input type="checkbox"/>	Semiconductor memory device and information device	365/189 .12
2	US 20010 00754 1 A1	<input type="checkbox"/>	Semiconductor memory device	365/233
3	US 20010 00513 2 A1	<input type="checkbox"/>	Semiconductor device testing method and system and recording medium	324/158 .1
4	US 66178 42 B2	<input type="checkbox"/>	Semiconductor device testing method and system employing trace data	324/158 .1
5	US 65494 75 B2	<input type="checkbox"/>	Semiconductor memory device and information device	365/189 .12
6	US 65047 89 B2	<input type="checkbox"/>	Semiconductor memory device	365/233
7	US 64250 47 B1	<input type="checkbox"/>	Process containing address decoders suited to improvements in clock speed	711/101
8	US 57614 90 A	<input type="checkbox"/>	Changing the meaning of a pre-decode bit in a cache memory depending on branch prediction mode	712/239
9	US 55069 70 A	<input type="checkbox"/>	Bus arbitrator circuit	710/113
10	US 54127 84 A	<input type="checkbox"/>	Apparatus for parallelizing serial instruction sequences and creating entry points into parallelized instruction sequences at places other than beginning of particular parallelized instruction sequence	712/245
11	US 54086 58 A	<input type="checkbox"/>	Self-scheduling parallel computer system and method	712/216
12	US 53476 39 A	<input type="checkbox"/>	Self-parallelizing computer system and method	712/203
13	US 44146 22 A	<input type="checkbox"/>	Addressing system for a computer, including a mode register	711/215

	Docum ent ID	U	Title	Current OR
1	US 20040 01975 6 A1	<input type="checkbox"/>	Memory device supporting a dynamically configurable core organization	711/170
2	US 20030 22329 3 A1	<input checked="" type="checkbox"/>	Synchronous type semiconductor memory device	365/200
3	US 20030 16451 0 A1	<input checked="" type="checkbox"/>	Redundancy architecture for repairing semiconductor memories	257/200
4	US 20030 13577 9 A1	<input checked="" type="checkbox"/>	Microprocessor	713/600
5	US 20030 12652 9 A1	<input checked="" type="checkbox"/>	Wafer burn-in test mode circuit	714/720
6	US 20030 10133 3 A1	<input checked="" type="checkbox"/>	Data processor	712/226
7	US 20030 08573 1 A1	<input checked="" type="checkbox"/>	Semiconductor device having test mode entry circuit	326/16
8	US 20030 08149 1 A1	<input checked="" type="checkbox"/>	SEMICONDUCTOR MEMORY DEVICE WITH REDUCED POWER CONSUMPTION	365/233
9	US 20030 07578 9 A1	<input checked="" type="checkbox"/>	Semiconductor storage device having memory chips in a stacked structure	257/678
10	US 20030 06153 6 A1	<input checked="" type="checkbox"/>	Power controlling method for semiconductor storage device and semiconductor storage device employing same	714/14
11	US 20030 02116 3 A1	<input type="checkbox"/>	Semiconductor memory device and information device	365/189 .12
12	US 20030 01445 7 A1	<input checked="" type="checkbox"/>	Method and apparatus for vector processing	708/520
13	US 20020 17107 5 A1	<input checked="" type="checkbox"/>	Register setting method and semiconductor device	257/10
14	US 20020 14592 9 A1	<input checked="" type="checkbox"/>	Control circuit and semiconductor memory device	365/222
15	US 20010 02342 4 A1	<input checked="" type="checkbox"/>	Exponent unit of data processing system	708/277
16	US 20010 00754 1 A1	<input type="checkbox"/>	Semiconductor memory device	365/233
17	US 20010 00513 2 A1	<input type="checkbox"/>	Semiconductor device testing method and system and recording medium	324/158 .1

	Document ID	v	Title	Current OR
18	US 66788 18 B1	<input checked="" type="checkbox"/>	Decoding next instruction of different length without length mode indicator change upon length change instruction detection	712/210
19	US 66752 90 B1	<input checked="" type="checkbox"/>	Processor for improving instruction utilization using multiple parallel processors and computer system equipped with the processor	712/229
20	US 66511 96 B1	<input checked="" type="checkbox"/>	Semiconductor device having test mode entry circuit	714/724
21	US 66314 63 B1	<input checked="" type="checkbox"/>	Method and apparatus for patching problematic instructions in a microprocessor using software interrupts	712/227
22	US 66178 42 B2	<input type="checkbox"/>	Semiconductor device testing method and system employing trace data	324/158 .1
23	US 65775 50 B2	<input checked="" type="checkbox"/>	Control circuit and semiconductor memory device	365/222
24	US 65747 27 B1	<input checked="" type="checkbox"/>	Method and apparatus for instruction sampling for performance monitoring and debug	712/227
25	US 65667 60 B1	<input checked="" type="checkbox"/>	Semiconductor storage device having memory chips in a stacked structure	257/777
26	US 65529 55 B1	<input checked="" type="checkbox"/>	Semiconductor memory device with reduced power consumption	365/233
27	US 65499 91 B1	<input checked="" type="checkbox"/>	Pipelined SDRAM memory controller to optimize bus utilization	711/158
28	US 65494 75 B2	<input type="checkbox"/>	Semiconductor memory device and information device	365/189 .12
29	US 65395 02 B1	<input checked="" type="checkbox"/>	Method and apparatus for identifying instructions for performance monitoring in a microprocessor	714/47
30	US 65047 89 B2	<input type="checkbox"/>	Semiconductor memory device	365/233
31	US 64929 92 B2	<input checked="" type="checkbox"/>	Graphic pattern processing apparatus	345/568
32	US 64876 29 B1	<input checked="" type="checkbox"/>	Semiconductor memory for operation in a plurality of operational modes	711/104
33	US 64635 18 B1	<input checked="" type="checkbox"/>	Generation of memory addresses for accessing a memory utilizing scheme registers	711/220
34	US 64532 78 B1	<input checked="" type="checkbox"/>	Flexible implementation of a system management mode (SMM) in a processor	703/27
35	US 64265 60 B1	<input checked="" type="checkbox"/>	Semiconductor device and memory module	257/777
36	US 64250 47 B1	<input type="checkbox"/>	Process containing address decoders suited to improvements in clock speed	711/101
37	US 64145 30 B2	<input checked="" type="checkbox"/>	Semiconductor integrated circuit device, semiconductor memory system and clock synchronous circuit	327/269
38	US 63817 20 B1	<input checked="" type="checkbox"/>	Test circuit and method for system logic	714/727
39	US 63811 90 B1	<input checked="" type="checkbox"/>	Semiconductor memory device in which use of cache can be selected	365/230 .03
40	US 63361 78 B1	<input checked="" type="checkbox"/>	RISC86 instruction set	712/23

	Docum ent ID	U	Title	Current OR
41	US 62928 48 B1	<input checked="" type="checkbox"/>	Computing system adapter card for supporting legacy and plug and play configurations	710/8
42	US 62085 63 B1	<input checked="" type="checkbox"/>	Semiconductor memory device which continuously performs read/write operations with short access time	365/189 .05
43	US 61417 42 A	<input checked="" type="checkbox"/>	Method for reducing number of bits used in storage of instruction address pointer values	711/220
44	US 60932 13 A	<input checked="" type="checkbox"/>	Flexible implementation of a system management mode (SMM) in a processor	703/27
45	US 60853 14 A	<input checked="" type="checkbox"/>	Central processing unit including APX and DSP cores and including selectable APX and DSP execution modes	712/213
46	US 60818 86 A	<input checked="" type="checkbox"/>	Holding mechanism for changing operation modes in a pipelined computer	712/229
47	US 60322 47 A	<input checked="" type="checkbox"/>	Central processing unit including APX and DSP cores which receives and processes APX and DSP instructions	712/35
48	US 60147 14 A	<input checked="" type="checkbox"/>	Adapter card system including for supporting multiple configurations using mapping bit	710/8
49	US 59915 31 A	<input checked="" type="checkbox"/>	Scalable width vector processor architecture for efficient emulation	703/26
50	US 59739 88 A	<input checked="" type="checkbox"/>	Semiconductor memory device having circuit for monitoring set value of mode register	365/230 .08
51	US 59266 42 A	<input checked="" type="checkbox"/>	RISC86 instruction set	712/1
52	US 59251 23 A	<input checked="" type="checkbox"/>	Processor for executing instruction sets received from a network or from a local memory	712/212
53	US 59207 13 A	<input checked="" type="checkbox"/>	Instruction decoder including two-way emulation code branching	712/236
54	US 59095 67 A	<input checked="" type="checkbox"/>	Apparatus and method for native mode processing in a RISC-based CISC processor	712/208
55	US 58939 27 A	<input checked="" type="checkbox"/>	Memory device having programmable device width, method of programming, and method of setting device width for memory device	711/171
56	US 58549 13 A	<input checked="" type="checkbox"/>	Microprocessor with an architecture mode control capable of supporting extensions of two distinct instruction-set architectures	712/210
57	US 58524 28 A	<input checked="" type="checkbox"/>	Display driving device	345/100
58	US 58190 56 A	<input checked="" type="checkbox"/>	Instruction buffer organization method and system	712/204
59	US 58092 73 A	<input checked="" type="checkbox"/>	Instruction predecode and multiple instruction decode	712/210
60	US 58023 60 A	<input checked="" type="checkbox"/>	Digital microprocessor device having dynamically selectable instruction execution intervals	712/229
61	US 57940 63 A	<input checked="" type="checkbox"/>	Instruction decoder including emulation using indirect specifiers	712/23
62	US 57937 75 A	<input checked="" type="checkbox"/>	Low voltage test mode operation enable scheme with hardware safeguard	714/724
63	US 57817 50 A	<input checked="" type="checkbox"/>	Dual-instruction-set architecture CPU with hidden software emulation mode	712/209

	Docum ent ID	U	Title	Current OR
64	US 57614 90 A	<input type="checkbox"/>	Changing the meaning of a pre-decode bit in a cache memory depending on branch prediction mode	712/239
65	US 57036 16 A	<input checked="" type="checkbox"/>	Display driving device	345/98
66	US 56637 45 A	<input checked="" type="checkbox"/>	Display driving device	345/98
67	US 56361 73 A	<input checked="" type="checkbox"/>	Auto-precharge during bank selection	365/230 .03
68	US 56301 61 A	<input checked="" type="checkbox"/>	Serial-parallel digital signal processor	712/36
69	US 55600 36 A	<input checked="" type="checkbox"/>	Data processing having incircuit emulation function	712/227
70	US 55308 04 A	<input checked="" type="checkbox"/>	Superscalar processor with plural pipelined execution units each unit selectively having both normal and debug modes	714/30
71	US 55069 70 A	<input type="checkbox"/>	Bus arbitrator circuit	710/113
72	US 54127 84 A	<input type="checkbox"/>	Apparatus for parallelizing serial instruction sequences and creating entry points into parallelized instruction sequences at places other than beginning of particular parallelized instruction sequence	712/245
73	US 54086 58 A	<input type="checkbox"/>	Self-scheduling parallel computer system and method	712/216
74	US 53964 98 A	<input checked="" type="checkbox"/>	Integrated circuit with peripheral test controller	714/703
75	US 53476 39 A	<input type="checkbox"/>	Self-parallelizing computer system and method	712/203
76	US 52805 93 A	<input checked="" type="checkbox"/>	Computer system permitting switching between architected and interpretation instructions in a pipeline by enabling pipeline drain	712/208
77	US 52261 64 A	<input checked="" type="checkbox"/>	Millicode register management and pipeline reset	712/209
78	US 51670 26 A	<input checked="" type="checkbox"/>	Simultaneously or sequentially decoding multiple specifiers of a variable length pipeline instruction based on detection of modified value of specifier registers	712/210
79	US 51485 28 A	<input checked="" type="checkbox"/>	Method and apparatus for simultaneously decoding three operands in a variable length instruction when one of the operands is also of variable length	712/210
80	US 51426 33 A	<input checked="" type="checkbox"/>	Preprocessing implied specifiers in a pipelined processor	712/225
81	US 51290 79 A	<input checked="" type="checkbox"/>	Computer system having subinstruction surveillance capability	712/211
82	US 51230 96 A	<input checked="" type="checkbox"/>	Data processor with addressing mode decoding function	712/212
83	US 50310 96 A	<input checked="" type="checkbox"/>	Method and apparatus for compressing the execution time of an instruction stream executing in a pipelined processor	711/169
84	US 45614 43 A	<input checked="" type="checkbox"/>	Coherent inductive communications link for biomedical applications	607/31
85	US 44146 22 A	<input type="checkbox"/>	Addressing system for a computer, including a mode register	711/215



	Docum ent ID	U	Title	Current OR
86	US 43441 29 A	<input checked="" type="checkbox"/>	Data processor system capable of providing both a computer mode and a sequencer mode of operation	712/229
87	US 41998 10 A	<input checked="" type="checkbox"/>	Radiation hardened register file	714/15
88	US 41077 81 A	<input checked="" type="checkbox"/>	Electronic calculator or microprocessor with indirect addressing	708/100
89	US 40842 35 A	<input checked="" type="checkbox"/>	Emulation apparatus	703/26
90	US 38184 60 A	<input checked="" type="checkbox"/>	EXTENDED MAIN MEMORY ADDRESSING APPARATUS	711/2
91	US 35771 90 A	<input type="checkbox"/>	APPARATUS IN A DIGITAL COMPUTER FOR ALLOWING THE SKIPPING OF PREDETERMINED INSTRUCTIONS IN A SEQUENCE OF INSTRUCTIONS, IN RESPONSE TO THE OCCURRENCE OF CERTAIN CONDITIONS	712/226